

Supertherm MG



Product Data Sheet

February 2021

Product description

Supertherm MG is a totally CFC/HCFC free, rigid polyisocyanurate foam insulation board, faced on both sides with mineral coated glass tissue.

Application

Rooftop: flat roof insulation for use with bitumen, mastic asphalt, single-ply or on adhesive bonded waterproofing systems.

Features and Benefits

- Totally CFC/HCFC free
- Full range of thicknesses to meet appropriate Building Regulations
- Lightweight and easy to handle
- High insulation value thermal conductivity 0.024-0.027 W/mK
- Rot proof, durable and maintenance free
- Tapered / cut-to-falls boards also available
- Zero Ozone Depletion Potential
- Global Warming Potential of less than 5

Product Technical Data

Board Size	1200mm x 1200mm or 1200mm x 600mm
Thermal Conductivity	0.024-0.027 W/mK
Compressive Strength	>150 kPa @ 10%
Density (foam core)	32 kg/m ³
Standard Thicknesses	25/30/40/50/60/70/80/90/100/120/140/150/160 mm
Standard Tapered Thicknesses	Slope 1/60: 30/50mm 50/70mm 70/90mm & 90/110mm

NB. Other thicknesses available to order.

Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued.

IKO Limited

14 Sanda Road, Whitehouse, Newtownabbey, County Antrim, BT37 9UB
Tel: 028 9086 7079 Fax: 028 9086 9079 E-mail: waterproofing@iko-ni.com

Unit 502, Northwest Business Park, Ballycoolin, Dublin, D15 CP3V
Tel: 01 8855090 Fax: 01 8855858 Email: waterproofing@iko.ie